



*Measurement and Reporting of Product Power Consumption according to ENERGY STAR Program Requirements for Imaging Equipment V2.0*

**Product Power Consumption Measurements on  
Lexmark CS725dte / C4150**

**General**

The Lexmark Acoustics and Energy Laboratory (AEL) is a source of product power consumption measurement and claims for Lexmark International, Inc. The AEL is a first party lab as recognized by the EPA and is accredited under ISO 17025. The lab performs measurement on all Lexmark products as well as products designed and manufactured by Lexmark for other Customers.

**Referenced Test Standards**

The product power consumption measurements were carried out in accordance with the following test protocols and standards

1. "ENERGY STAR Program Requirements for Imaging Equipment , V2.0"
2. "ENERGY STAR Test Method for determining Imaging Equipment Energy Use V2.0 October 2014"

**Measurement Equipment**

The following measurement equipment is used in the power consumption testing. All measurement equipment is calibrated on an annual basis.

Equipment	Type	Accuracy	Date of Last Calibration
Universal Power Analyzer	Yokogawa WT1600	0.2% of Range	2014-10-01 <i>(Equipment is calibrated every 12 months)</i>
AC Power Source	Pacific Power Source Corp, Model AMX-360	Voltage: 0.03% of Command Voltage Frequency: 0.01 Hz Load Regulation 0.25% Max THD: 0.1% , Response time: 5µs	Factory Cal Only <i>Annual Calibration not required as Power Analyzer Verifies AC Source</i>

**Environmental Conditions in Test Room during Test**

- Temperature: 21.8 to 22.7°C
- Relative Humidity: 51 to 59%
- Barometric Pressure: 97.6 to 98.5kPa
- Ambient Wind Speed <0.5m/s



This report may not be used to imply ilac or A2LA endorsement of the product.

The results reported here relate only to the specific items tested and to the specific configurations and conditions tested.

This report shall not be reproduced, except in full, without the written approval of the Lexmark Acoustics and Energy Laboratory





Lexmark™

Lexmark Acoustics and Energy Laboratory

20150819-191-ES

Acoustics and Energy Laboratory  
Bldg 032-2, Room 10D1-2  
740 West New Circle Road  
Lexington, Kentucky 40550

September 2, 2015

Page 2 of 4

*Measurement and Reporting of Product Power Consumption according to ENERGY STAR Program Requirements for Imaging Equipment V2.0*

**Test Information and Operating Conditions**

Product under Test	Lexmark CS725dte / C4150		
Product Type	Color Electrophotographic Printer		
Operating Condition	Product was tested in the factory default condition.		
Paper Type	Paper Used in TEC testing follows Requirements in Reference [2]		
Testing Voltage Measured	<input checked="" type="checkbox"/> 100V / 50 Hz	<input checked="" type="checkbox"/> 115 V / 60 Hz	<input checked="" type="checkbox"/> 230 V / 50 Hz
Rated Speed	50 ppm Monochrome , 50 ppm Color		
Power Supply Type	Internal Power Supply (AC-DC)		
Interfaces used during Test	Connected interfaces follow the priority given in Table 6 of [2] <input type="checkbox"/> USB 2.0 <input checked="" type="checkbox"/> 1 GB Wired Ethernet <input type="checkbox"/> 100 MB Wired Ethernet <input type="checkbox"/> Analog Fax (Ring Down Simulator)		
IEEE 802.3Az	<input checked="" type="checkbox"/> On	<input type="checkbox"/> Off	
Product Format	<input type="checkbox"/> Small	<input checked="" type="checkbox"/> Standard, Not A3	<input type="checkbox"/> Standard, A3
Calculated Measurement Uncertainty	<input checked="" type="checkbox"/> Meets $\leq 2\%$ requirement		
"Optional" Accessories attached to base Product	550 sheet tray		
Service / Maintenance Modes	<input checked="" type="checkbox"/> None <input type="checkbox"/> Present, but disabled for the Test		
Duplex Present	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> Optional
Features Present	<input type="checkbox"/> Digital Front End <input type="checkbox"/> Cordless Handset <input type="checkbox"/> External Power Supply		
Serial Numbers	100 V	115 V	230 V
	40C90005028PTBCOB146	40C90005028PTBCOB146	40C90005028PTBCOB146
Test IDs	T241_37 through T241_58		M241_7 through M241_19
Date(s) of Test	2015-08-03 through 2015-08-26		
Test Performed by	M. Mohon		

**Measurement Results**

The measurement results are measured according to the testing documents referenced in the ENERGY STAR Program Requirements for Imaging Equipment V2.0 and Imaging Equipment Test Method for Determining Imaging Equipment Energy Use V2.0-October 2014.



This report may not be used to imply ilac or A2LA endorsement of the product.

The results reported here relate only to the specific items tested and to the specific configurations and conditions tested.

This report shall not be reproduced, except in full, without the written approval of the Lexmark Acoustics and Energy Laboratory





### Measurement and Reporting of Product Power Consumption according to ENERGY STAR Program Requirements for Imaging Equipment V2.0

**Table 1:** ENERGY STAR TEC Test and Evaluation for Printers, Digital Duplicators and MFDs – ENERGY STAR Imaging Equipment V2.0 Requirements (Roman numerals indicate particular critical-component configurations detailed in Table 2)

		100 V / 50 Hz	115 V / 60 Hz	230 V / 50 Hz
1	"Off/Hibernate Interval" Energy (Watt – hour)	0.119	0.127	0.210
2	"Off Interval" Time (minutes)	10.00	10.00	10.00
3	"Active0" Time (seconds)	7.60	6.57	6.64
5	"Sleep Interval" Energy <sup>y</sup> (Watt – hour)	2.176	2.195	2.230
	"Sleep Interval" Time (minutes)	60.00	60.00	60.00
6	"Job1 Interval" Energy (Watt – hour)	13.992	13.474	13.315
	"Active1" Time (seconds)	21.20	19.08	19.19
7	"Job2 Interval" Energy (Watt – hour)	12.835	12.826	13.069
	"Active2" Time (seconds)	19.05	19.05	18.16
8	"Job3 Interval" Energy (Watt – hour)	12.466	12.565	12.464
9	"Job4 Interval" Energy (Watt – hour)	12.324	12.464	12.292
10	"Final Interval" Energy (Watt – hour)	0.073	0.073	0.074
	"Final Interval" Time (minutes)	2.00	2.00	2.00
TEC	Calculated TEC Value (KWh)	<b>2.30</b>	<b>2.31</b>	<b>2.31</b>
TEC	Limits (KWh)	<b>7.85</b>		
Percent [Calculated TEC Value / Limits ]		29.3%	29.4%	29.4%



This report may not be used to imply ilac or A2LA endorsement of the product.

The results reported here relate only to the specific items tested and to the specific configurations and conditions tested.

This report shall not be reproduced, except in full, without the written approval of the Lexmark Acoustics and Energy Laboratory





**Lexmark**<sup>TM</sup>

**Lexmark Acoustics and Energy  
Laboratory**

20150819-191-ES

Acoustics and Energy Laboratory  
Bldg 032-2, Room 10D1-2  
740 West New Circle Road  
Lexington, Kentucky 40550

September 2, 2015

Page 4 of 4

*Measurement and Reporting of Product Power Consumption according to ENERGY  
STAR Program Requirements for Imaging Equipment V2.0*

Authored by: 

Marc Mohon  
AEL Energy Test Specialist/ Quality Technician  
AEL (Acoustics and Energy Laboratory)  
Lexmark International, Inc.

Reviewed and Approved by: 

Scott Searls  
AEL Energy Testing and Quality Manager,  
AEL (Acoustics and Energy Laboratory)  
Lexmark International, Inc.

*The results reported here relate only to the specific items tested and to the specific configurations tested. This report shall not be reproduced, except in full, without the written approval of the Lexmark Acoustics and Energy Laboratory.*



This report may not be used to imply ilac or A2LA endorsement of the product.

The results reported here relate only to the specific items tested and to the specific configurations and conditions tested.

This report shall not be reproduced, except in full, without the written approval of the Lexmark Acoustics and Energy Laboratory



**Lexmark CS725dte**